

LUG NUT TORQUE SPECIFICATIONS

Stud Size	Lug Nut Type	Torque Specifications	Wheel Size & Type	Wheel Material
1/2"	Coned	90-120 ft.-lb.	15"	Steel
1/2"	Coned	90-120 ft.-lb.	16"	Steel
9/16"	Coned	120-140 ft.-lb.	16"	Steel
5/8"	Coned w/Wheat Clamp Ring	190-210 ft.-lb.	17.5" Single or 16" Dual	Steel
5/8"	Flanged Nuts (Non-Rotating Flange)	275-325 ft.-lb.	17.5" Single or 16" Dual	Steel
5/8"	Flanged Nuts (Rotating Flange)	190-210 ft.-lb.	17.5" Single or 16" Dual	Steel
1/2"	Coned	90-100 ft.-lb.	15"	Aluminum
1/2"	Coned	90-100 ft.-lb.	16"	Aluminum
9/16"	Coned	120-140 ft.-lb.	16"	Aluminum
9/16"	Coned	130-150 ft.-lb.	17.5"	Aluminum
5/8"	Coned	140-160 ft.-lb.	17.5"	Aluminum
5/8"	Flanged Nuts (Rotating Flange)	150 ft.-lb.	16"	Aluminum